

Technical Specifications

Pattern	Size	PR	Type	Dimension (mm)				Rim	Fitment	Load Index	Extra Load	Max. Load (kg)	Pressure (Psi)	Speed Index	Speed (km/h)	Picture
				OD	SW	OTD	TW									
AH51	295/80R22.5	18	TL	1048	300	14.9	246	9.00 x 22.5	Single	154		3750	123	M	130	
									Dual	149		3250	123			
AH31	315/80R22.5	20	TL	1079	310	17.5	260	9.00 x 22.5	Single	156	154	4125	130	L/M	120/130	
AH31K	11R22.5	16	TL	1049	274	15.5	219	8.25 x 22.5	Single	148		3150	123			
AH31+	295/80R22.5	16	TL	1052	306	16.5	250	9.00 x 22.5	Dual	145		2900	123	M	130	
AH35	225/75R17.5	12	TL	787	232	12.1	194	6.75 x 17.5	Single	129		1850	105			
	215/75R17.5	14	TL	771	218	12.6	188	6.00 x 17.5	Dual	127		1750	105	M	130	
									Single	128		1700	102			
	750R16	14	TT	803	208	11.2	144	6.00 x 16	Dual	126		1600	102	L	120	
									Single	123		1550	110			
	750R16	16	TT	803	208	13.1	149	6.00 x 16	Dual	119		1360	110	L	120	
									Single	123		1600	110			
	AH30	1000R20	18	TT	1051	274	15	210	7.50 x 20	Dual	119		1450	110	K	110
1100R20		18	TT	1080	290	15.5	216	8.00 x 20	Single	149		3250	135	J		
									Dual	146		3000	135	K	110	
1200R24		20	TT	1204	310	14	230	8.50 x 24	Single	150		3350	120			K
									Dual	147		3075	120			
325/95R24		22	TT	1204	310	14	230	9.00 x 24	Single	160		4500	125	K	110	
									Dual	156		4000	125			
AU04		11R22.5	16	TL	1057	274	20.4	214	8.25 x 22.5	Single	162		4750	125	J	100
	Dual									160		4500	125			
AU06	275/70R22.5	18	TL	967	279	18.9	230	8.25 x 22.5	Single	148		3000	120	J	100	
									Dual	145		2725	120			
AM09	1200R24	20	TT	1216	310	16.5	222	8.50 x 24	Single	150	152	3350	131	J/F	100/80	
									Dual	145	148	2900	131			
AM81	1000R20	16	TT	1053	270	15.5	210	7.50 x 20	Single	160		4500	125	K	110	
									Dual	156		4000	125			
DM06	1000R20	16	TT	1053	270	15.5	210	7.50 x 20	Single	146		3000	120	K	110	
	1100R20	16	TT	1081	286	16	216	8.00 x 20	Dual	143		2725	120			
									Single	150		3350	120	K	110	
	1200R20	18	TT	1120	306	16.5	232	8.50 x 20	Dual	147		3075	120			
									Single	154		3750	120	K	110	
	Dual	151		3450	120											

Technical Specifications

Pattern	Size	PR	Type	Dimension (mm)				Rim	Fitment	Load Index	Extra Load	Max. Load (kg)	Pressure (Psi)	Speed Index	Speed (km/h)	Picture
				OD	SW	OTD	TW									
DM80D	1000R20	16	TT	1058	274	18.5	208	7.50 x 20	Single	146		3000	120	K	110	
									Dual	143		2725	120			
DM04	750R16	14	TT	809	208	16	170	6.00 x 16	Single	122		1500	102	F	80	
									Dual	121		1450	102			
	1000R20	16	TT	1068	271	23.5	215	7.50 x 20	Single	146		3000	120	G	90	
									Dual	143		2725	120			
	1100R20	16	TT	1096	286	23.5	235	8.00 x 20	Single	150		3350	120	G	90	
									Dual	147		3075	120			
	1200R20	18	TT	1132	304	22	240	8.50 x 20	Single	154		3750	120	G	90	
									Dual	151		3450	120			
	1200R24	18	TT	1225	310	20.9	245	8.50 x 24	Single	156		4250	120	G	90	
									Dual	153		3875	120			
	11R22.5	16	TL	1070	278	24.5	220	8.25 x 22.5	Single	148		3000	120	K	110	
									Dual	145		2725	120			
	12R22.5	18	TL	1098	300	25	235	9.00 x 22.5	Single	152		3550	135	G	90	
									Dual	149		3250	135			
	13R22.5	18	TL	1136	322	23	245	9.75 x 22.5	Single	154	156	4000	127	K/G	110/90	
									Dual	150	150	3350	127			